

LETTER • OPEN ACCESS

Early retirement of power plants in climate mitigation scenarios

To cite this article: Robert Fofrich *et al* 2020 *Environ. Res. Lett.* **15** 094064

View the [article online](#) for updates and enhancements.

You may also like

- [SDG implications of water-energy system transitions in India, for NDC, 2 °C, and well below 2 °C scenarios](#)
Saritha Sudharma Vishwanathan, Amit Garg, Vineet Tiwari et al.
- [Recalibrating climate prospects](#)
Amory B Lovins, Diana Ürge-Vorsatz, Luis Mundaca et al.
- [Plasmoid drift and first wall heat deposition during ITER H-mode dual-SPIs in JOREK simulations](#)
D. Hu, F.J. Artola, E. Nardon et al.

Environmental Research Letters



LETTER

Early retirement of power plants in climate mitigation scenarios

OPEN ACCESS

RECEIVED
22 January 2020

REVISED
5 May 2020

ACCEPTED FOR PUBLICATION
27 May 2020

PUBLISHED
27 August 2020

Original content from
this work may be used
under the terms of the
[Creative Commons
Attribution 4.0 licence](#).

Any further distribution
of this work must
maintain attribution to
the author(s) and the title
of the work, journal
citation and DOI.



Robert Fofrich¹ , Dan Tong¹, Katherine Calvin² , Harmen Sytze De Boer^{3,4}, Johannes Emmerling⁵ , Oliver Fricko⁶, Shinichiro Fujimori^{6,7,8} , Gunnar Luderer^{9,10} , Joeri Rogelj^{6,11} and Steven J Davis^{1,12}

- ¹ Department of Earth System Science, University of California at Irvine, Irvine, CA, United States of America
- ² Joint Global Change Research Institute, Pacific Northwest National Laboratory, College Park, MD, United States of America
- ³ PBL Netherlands Environmental Assessment Agency, 2594 AV The Hague, The Netherlands
- ⁴ Copernicus Institute for Sustainable Development, Utrecht University, Utrecht, The Netherlands
- ⁵ RFF-CMCC European Institute on Economics and the Environment (EIEE), Centro Euro-Mediterraneo sui Cambiamenti Climatici, Via Bergognone 34, I-20144 Milan, Italy
- ⁶ Energy Program, International Institute for Applied Systems Analysis (IIASA), 2361, Laxenburg, Austria
- ⁷ Center for Social and Environmental Systems Research, National Institute for Environmental Studies (NIES), Tsukuba, Japan
- ⁸ Department of Environmental Engineering, Graduate School of Engineering, Kyoto University, Nishikyo-ku, Japan
- ⁹ Potsdam Institute for Climate Impact Research (PIK), Member of the Leibniz Association, Potsdam, Germany
- ¹⁰ Chair of Global Energy Systems, Technische Universität Berlin, Straße des 17. Juni 135, 10623 Berlin, Germany
- ¹¹ Grantham Institute for Climate Change and the Environment, Imperial College London, London, United Kingdom
- ¹² Department of Civil and Environmental Engineering, University of California at Irvine, Irvine, CA, United States of America

E-mail: rfofrich@uci.edu

Keywords: climate change, energy systems, power plants, representative concentration pathways, integrated assessment model, shared socioeconomic pathways, climate policy

Supplementary material for this article is available [online](#)


Abstract

International efforts to avoid dangerous climate change aim for large and rapid reductions of fossil fuel CO₂ emissions worldwide, including nearly complete decarbonization of the electric power sector. However, achieving such rapid reductions may depend on early retirement of coal- and natural gas-fired power plants. Here, we analyze future fossil fuel electricity demand in 171 energy-emissions scenarios from Integrated Assessment Models (IAMs), evaluating the implicit retirements and/or reduced operation of generating infrastructure. Although IAMs calculate retirements endogenously, the structure and methods of each model differ; we use a standard approach to infer retirements in outputs from all six major IAMs and—unlike the IAMs themselves—we begin with the age distribution and region-specific operating capacities of the existing power fleet. We find that coal-fired power plants in scenarios consistent with international climate targets (i.e. keeping global warming well-below 2 °C or 1.5 °C) retire one to three decades earlier than historically has been the case. If plants are built to meet projected fossil electricity demand and instead allowed to operate at the level and over the lifetimes they have historically, the roughly 200 Gt CO₂ of additional emissions this century would be incompatible with keeping global warming well-below 2 °C. Thus, ambitious climate mitigation scenarios entail drastic, and perhaps un-appreciated, changes in the operating and/or retirement schedules of power infrastructure.

Introduction

Among scenarios that succeed in stabilizing global mean temperatures at less than 2 °C warmer than the preindustrial era, CO₂ emissions from the power sector decrease rapidly in the coming decades, in almost all cases reaching net-zero before mid-century [1–5]. Such rapid and complete decarbonization

entails similarly rapid turnover of historically long-lived electricity-generating infrastructure. Coal- and gas-fired power plants have historically operated for 39 and 36 years (s.d.14 and 13 years), respectively [6]. However, in Integrated Assessment Models (IAMs), the decision of when to retire a generator is primarily economic, e.g. based on marginal operating costs, revenues, and the levelized costs of




new generating infrastructure [7–9]. IAM mitigation scenarios reconcile these economics with swift decarbonization of the electricity sector by modeling both policy-driven increases in the operational costs of CO₂-emitting power plants and rapidly decreasing costs of non-emitting sources of electricity [10, 11]. In reality, lawmakers may follow a similar approach, incentivizing the early closure of plants or severely reducing their operating hours by imposing strict regulations that increase their operating costs relative to non-emitting competitors. Examples of specific policies include setting a price on carbon, disallowing major maintenance (e.g. New Source Review in the United States), or subsidizing non-emitting technologies (e.g. renewable production tax credits). However, economics are not the sole determinant of power plant retirements, as there are numerous examples of fossil power plants now operating at a loss [12–14]. This suggests that more direct regulations such as an outright ban of a given fossil technology or mandating the early closure of certain power plants may be necessary. Nonetheless, given the initial capital costs of fossil fuel electricity generating capacity are typically \$200–5000 per kW and installed fossil capacity worldwide is today ~4000 GW [9, 15, 16], the premature retirement of power generating infrastructure could result in the loss of trillions of dollars of capital investment and future returns, and perhaps even jeopardize the stability of financial systems if not adequately managed and anticipated [17–20]. Moreover, losses from early retirement of fossil electricity generating assets may ultimately be borne by the rate- and tax-paying populace. For these reasons, the socioeconomic and political repercussions that arise from very early retirement of coal- and gas-fired power plants may be challenging to overcome.

Several previous studies have estimated the CO₂ that will be emitted by existing and proposed energy

infrastructure if it is operated for historical average lifetimes [6, 8, 16]. Others have used IAMs in various ways: using scenarios as a guide to future fossil capacity [21], adding plant lifetime as an exogenous constraint within a model [22], or evaluating the infrastructural inertia of emissions in a designed multi-model experiment [23]. However, prior work has generally focused on differences in emissions related to the lifetime, operation, or commissioning of generating infrastructure. Here, we also take the opposite perspective: what do the rapid emissions reductions in mitigation scenarios imply for the lifetime, operation, and commissioning of generating infrastructure? Specifically, how severely must the lifetime or operation of power plants be abbreviated or curtailed, respectively, in order to achieve the emissions decreases (i.e. mitigation rates) in different scenarios and regions? Although the answers to these questions can be explicitly calculated by some IAMs, modeling approaches between IAM vary, retirements are endogenous to the models, and retirement rates are not reported—or even tracked—by all modeling groups.

Here, using detailed data of currently existing power plants worldwide [24] in addition to electricity and emissions outputs from six major integrated assessment models, we analyze coal- and natural gas-fired power plant utilization rates and lifetimes as embedded in 171 recent scenarios, spanning three levels of emissions mitigation (1.9, 2.6, and 4.5 W m⁻² of radiative forcing; i.e. trajectories likely to avoid 1.5 °C, 2 °C, and 3 °C of mean warming this century), and five different socioeconomic trajectories (SSPs) [25]. We explicitly exclude oil-fired power generators from our analysis since they compose less than 5% of global electricity generating capacity [26]. Further details of our analytic approach are in the *Methods* and *supplementary information* (available online



at (stacks.iop.org/ERL/15/094064/mmedia). Figure 1 summarizes how our analyses were conducted schematically. In this figure we only show the simplest approach to facilitate the readers understanding

of our methodology. Here we assume a uniform operating lifetime (e.g. 40 years in figure 1(a)) and capacity factor (e.g. 70% in figure 1(a)). In addition, we evaluate whether and when fossil fuel- and




Figure 3. Annual mean emission mitigation rates, cumulative emissions and emission overshoot in energy-emission scenarios. Cumulative CO₂ emissions from coal- and gas-fired power plants in the 1.9, 2.6, and 4.5 W m⁻² radiative forcing trajectories over the 21st century (a–c). Cumulative emissions increase as power plants lifetimes are prolonged and as climate mitigation goals wane. Annual emission reductions from coal and gas electrical generators decline with an increase in assumed power plant lifetime and with increased inertia from electricity production (d–f). Differences between SSP emissions projections and emissions under different lifetime assumptions (g–i). Dashed vertical line indicates the historical mean lifetime whereas the white dashed line is the cumulative emission mean across all IAM-SSPs for each of the forcing scenarios. Color intensity indicates the 50th–95th percentile cumulative emissions for all of the IAM-SSPs. The light horizontal line represents the median cumulative emission overshoot value, if power plants follow historical mean lifetime trends. The cumulative emission overshoot under different lifetime assumptions decreases as the radiative imbalance increases.


region-specific electricity demand in each IAM scenario (black curves) will require new capacity to be commissioned (colored squares) if existing capacity (gray squares) is not able to meet the projected fossil electricity need. As fossil electricity demand declines within the IAMs in the future, we quantify the extent to which there would be excess generating capacity given the assumed lifetime and capacity factor of operating power plants (black-hatched squares). By further assuming a carbon emissions factor (CO₂ per unit electricity generated) in line with historical estimates, we can in turn quantify the potential emissions associated with such excess capacity. Assumed lifetime, capacity factor, and carbon emission factors are varied in repeated analyses (e.g. figures 1(b) and (c)). We analyze model projections using fixed lifetimes and capacity factors to project all plausible values of future emissions. Additionally, we vary power

plant operating conditions in each subsequent annual time step as a sensitivity test for our results. However, this added flexibility to the initial operational conditions of power generating infrastructure had very little impact on our overall results. For context, table 1 compares operating conditions and constraints on infrastructure retirements within each of the six IAMs.

In figure 2, the black curves show the annual CO₂ emissions from coal- and gas-fired electricity generation, as projected by the integrated assessment models, for all SSPs under different levels of future warming used in this study (i.e. radiative forcing of 1.9, 2.6, and 4.5 W m⁻²). In comparison, colored curves show our calculated emissions if power plant lifetimes are assumed to be 10, 20, 30, 40, 50, or 60 years (purple, blue, green, yellow, orange, and red, respectively). Here we also assume historical mean capacity

Table 1. Integrated Assessment Model Assumptions. Regional averaged values for each of the integrated assessment models used within this study. However, as the IAMs continue to evolve so do the underlying parameters. Thus, values represented in this table may change over time as newer versions of IAMs are released.


| | Lifetime (years) | Capacity factor (maximum/minimum) | Depreciation of capital rate (average percent per year) | Carbon intensity (range across technologies, regions, years, and SSPs) |
|-----------------|-----------------------------------------------|--------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Coal | | | | |
| AIM/CGE | 35 | 60% | 4% | Different across regions |
| GCAM | 60 | 80%–85% depending on type of plant | | 643 to 1233 gCO ₂ per kWh, depending on technology, region, year |
| IMAGE | 40 | Depending on relative operational costs (~85% till 0%) | Capacity gets retired after 40 ± 5 years of operation | Different per region, year, technology |
| MESSAGE-GLOBIOM | 30 | 67%–85% | 5% | 724–1302 gCO ₂ per kWh |
| REMIND-MAGPIE | 40 | 75%–80% | Non-linear | Different per region, year, technology; regional fleet averages of 738–1140 g kWh ⁻¹ in 2015 |
| WITCH-GLOBIOM | 40 | 85% | 2.8% | 699 to 1390 gCO ₂ kWh ⁻¹ , depending on technology, region, year |
| Gas | | | | |
| AIM/CGE | 30 | 70% | 4% | Different across regions |
| GCAM | 60 for existing gas plants, 45 for new plants | 80%–85% depending on type of plant | | 274 to 720 gCO ₂ per kWh, depending on technology, region, year |
| IMAGE | 40 | Depending on relative operational costs (~90% till 0%) | Capacity gets retired after 40 ± 5 years of operation or via early retirement in case of relatively high operational costs | Different per region, year, technology |
| MESSAGE-GLOBIOM | 30 | 58%–85% | 5% | 260–850 gCO ₂ kWh ⁻¹ |
| REMIND-MAGPIE | 35 | 55%–65% | Non-linear | Different per region, year, technology; regional fleet averages of 328–547 g kWh ⁻¹ in 2015 |
| WITCH-GLOBIOM | 25 | 70% | 4.4% | 354 to 1000 gCO ₂ kWh ⁻¹ , depending on technology, region, year |



and carbon emissions factors, see tables S1–6, however we vary power plant operational conditions in subsequent calculations to test impacts on our results. In all cases, bold curves represent the median of all global integrated assessment model scenarios ($n = 171$).

We see the median IAM emissions (black curves) generally decrease more quickly than the emissions

we estimate if plants were to operate for more than 30 years (green curves), especially in the case of coal-fired plants and under the more ambitious (lower warming) scenarios (figure 2). For example, figure 2(a) shows that median emissions, assuming coal-fired generator lifetimes greater than 30 years, do not decline as rapidly as the median IAM projections (bold black curve) for the 1.9 W m⁻² scenario. The



differences between the black IAM curves and our calculated curves reflects the magnitude of such excess emissions, which consistently increase as longer lifetimes are considered. However, the scenarios from different IAMs and SSPs can result in considerably different cumulative emissions, with greater model spread under higher warming scenarios (from left to right in figures 3(a)–(c)). For instance, in the lower warming (i.e. likely to avoid 1.5 °C and 2 °C) scenarios, cumulative emissions averaged across models and assumed lifetimes are greatest for SSP2 (‘middle-of-the-road’; blue), followed by SSP5 (‘fossil-fueled development’; pink) and least for SSP1 (‘sustainability’; green) and SSP4 (‘inequality’; pale orange). See *Methods* or ref [27] for further discussion on how the SSPs differ. Averaging across models, for a given lifetime, cumulative emissions vary by 27%, 30%, and 36% across SSPs in the different warming scenarios, respectively. In comparison, the average variation in cumulative emissions among models for a given SSP and lifetime are 31%, 45%, and 48% in the different warming scenarios, respectively.

The longer the assumed lifetime of power plants, the lower mean mitigation rates (defined here as the annual percent reduction in CO₂ emissions from 2017–2050) will be, figures 3(d)–(f). Since mean mitigation rates are inversely related to future warming, this relationship illustrates the temporal constraints imposed by infrastructural inertia. For example, in the scenarios likely to bring back warming to below 1.5 °C by 2100 (SSPx-1.9 scenarios from ref. [11]), integrated assessment model outputs average 6% per year reductions in emissions from coal- and gas-fired power plants (dotted gray line), but mean mitigation

rates when assuming plant lifetimes of 30 or more years decrease to <3% per year (figure 3(d)). Similarly, model outputs average 3.7% per year reductions in scenarios likely to avoid 2 °C (SSPx-2.6, dotted gray line), but mean mitigation rates when assuming plant lifetimes of 30 or more years decrease to <2% per year (figure 3(e)). Thus, allowing fossil-fired power infrastructure to operate for more than 30 years from initial commissioning is incompatible with the rapid mitigation rates achieved in the IAMs.

Since climate change is proportional to society’s cumulative emissions, we were interested in quantifying the amount of emissions over the IAMs (hereby ‘cumulative overshoot’) when power generators are operated for different periods of time. We find the cumulative overshoot increase along with assumed lifetimes but are also substantially greater in the lower warming scenarios (figures 3(g)–(i)). For instance, if we assume power generators will follow historical operating norms, a lifetime of 37 years and mean capacity factor (dashed lines), the cumulative overshoot rises from a median 112 Gt CO₂ in 4.5 $W m^{-2}$ scenarios, to 188 Gt CO₂ in 2.6 $W m^{-2}$ scenarios, to 220 Gt CO₂ in 1.9 $W m^{-2}$ scenarios. Given that total cumulative emissions averages just 182.5 Gt CO₂ in 1.9 $W m^{-2}$ scenarios, an additional 220 Gt CO₂ represents an overshoot of 220.5% and is roughly equivalent to the entire fossil electricity CO₂ budget in the 2.6 $W m^{-2}$ scenario. We find the similarity between the 1.9 and 2.6 $W m^{-2}$ scenarios (figure 4) largely result from the age distribution of the existing power fleet. In both cases, the IAM scenarios result in immediate reductions to global CO₂ emissions but do not consider the power infrastructure lifetimes of operating plants. Using our methods, but

following the 2.6 W m^{-2} scenario requires modest deployment of new fossil capacity resulting in a similar overshoot. Nonetheless, these findings indicate the extent to which the low cumulative emissions in ambitious mitigation scenarios are the result of early retirement of coal- and gas-fired power plants. In addition, the similarity of the IAM electricity pathways while achieving different levels of radiative forcing indicate that a substantial reduction of annual CO_2 emissions from other industries is required to reach the 1.9 W m^{-2} pathway. Figure 5 highlights the full range of power plant retirements under a range of capacity factor assumptions. If coal and gas power plant operations are severely curtailed, and climate mitigation targets are relaxed, then these plants may operate at similar lifetimes as they have historically. In contrast, these plants would have to retire decades earlier than they have in the past if we are to meet more ambitious climate warming trajectories.

In turn, supplementary figure 1 shows how key regions contribute to the cumulative overshoot in lower warming scenarios (averaging across the values for 1.9 and 2.6 W m^{-2} shown in figures 3(g) and (h)). In comparison to the other regions shown, overshoots increase most dramatically in China when longer lifetimes of power plants are assumed. This is consistent with previous unit-level inventories of emissions which have shown that half of now-existing coal-fired generating capacity is in China, and mostly <15 years old [28]. Supplementary figure S1(a) reveals the extent to which model scenarios anticipate the retirement of these Chinese plants before they reach 20 years of age. Similarly, early retirements are required to avoid substantial overshoots in other regions, but the magnitude of overshoot when an historical lifetime of 37 years is assumed are roughly 53%, 26% and 87% less in India, the U.S. and Western Europe than in China, respectively.

Supplementary figure 2 acts as sensitivity test to our projected emissions from allowing additional flexibility in initial power plant operational conditions. For example, varying assumptions of plant lifetime and capacity factor by 25% has a similar effect on estimated cumulative emissions, regardless of radiative forcing or SSP (Supplementary figure S2). However, both lifetime and capacity factor become less important in higher warming scenarios, and the assumed carbon intensity of electricity becomes a dominant factor (Supplementary figure S2).

1. Discussion and conclusions

Our results suggest that climate scenarios which are stabilize global temperatures in the range of $1.5 \text{ }^\circ\text{C}$ to $2 \text{ }^\circ\text{C}$ or below, retire coal- and gas-fired plants decades before their technical or historical lifetimes have been reached. Although it is generally understood that CO_2 emitting infrastructure will need to be swiftly decommissioned in order to mitigate the most

extreme consequences of climate change, the extent to which climate mitigation scenarios rely on the premature retirement of existing plants and the curtailment of future construction is not widely known. Since IAMs conduct power plant retirements endogenously, the rates and processes that dictate these retirements seem obscure to many who wish to interpret IAM results [29]. In addition, the IAM projections typically begin in 2005 and without incorporating information about the current installed fossil capacity or age distribution of fossil fuel-fired plants. Thus, climate mitigation scenarios may underestimate the inertia of emitting infrastructure. As a result of the IAM structure, the operating power capacity and projected mitigation rates in their scenarios can quickly diverge from the realities of the existing fossil fleet and can vary greatly between IAMs and SSPs.

The mitigation rates observed within IAMs are unprecedented and thus represent a potential challenge to society, particularly with the continued deployment of coal-fired power plants around the globe [30]. If coal-fired power generators are not retired early (or their capacity factors drastically reduced), then mitigation rates will fall behind IAM scenarios (figures 3(d) and (e)) and cumulative emissions will rise sharply (figures 3(a), (b), (g), and (h)), thus undermining the ability to achieve lower-warming targets without additional compensatory decreases in emissions from other sources [26, 27]. Although negative emissions are represented within the integrated assessment models, our results highlight that longer power plant lifetimes would require an even larger negative emissions than the prodigious quantities already present in some of the more ambitious mitigation scenarios (which are in some cases many Gt CO_2 per year) [31]. Moreover, the need for shortened infrastructure lifetimes is particularly critical in China, where coal-fired generating capacity is both young and large [16].

Given the established relationship of cumulative carbon budgets and climate warming [32–35], prior studies have estimated and compared ‘committed’ emissions over the expected lifetime of emitting infrastructure [6, 8, 16, 36]. Many climate mitigation scenarios thus optimize operating and retirement schedules of fossil-fueled infrastructure to lower their cumulative carbon emissions (hence attaining lower carbon budgets and establishing lower warming trajectories) by prioritizing economic conditions where costs of the power sector are equal to revenues from electrical generation rather than reflecting the inertia of the power fleet which is already in existence today. In actuality, decommissioning trillions of dollars’ worth of privately-owned capital after only 25% of its anticipated life has elapsed will present enormous political and economic challenges. Indeed, it is these challenges, collectively, that represent the infrastructural inertia (i.e. carbon lock-in) [9, 16, 36].

While the IAMs serve as a powerful tool, allowing users to gain insight regarding a particular sector, the mechanisms behind endogenous calculations are often seen as black boxes by the broader scientific community leading some to question their methods as inscrutable [29]. Thus, by using a standardized method to quantify the implicit lifetimes of power plants within these climate mitigation scenarios, our analysis provides a transparent process while demonstrating the extent to which lower warming scenarios may be contingent upon the early retirement of power sector infrastructure. In many cases, deliberately planned retirement of coal- and gas-fired power plants are necessary in mitigation scenarios which project limited growth in demand for fossil-fuel electricity. If instead, the deployment of fossil fuel power capacity is continued in the upcoming years, stabilizing global mean temperatures at less than 2 °C relative to the preindustrial will require even shorter retirement ages than those achieved within climate mitigation scenarios. Nonetheless, our results suggest that these targets can only be achieved through a strategic manipulation of installed coal- and gas-fired power capacity, generator lifetimes, and capacity factors (e.g. retiring certain plants prematurely or severely curtailing their usage while extending the lifetime of others until renewable electricity generating technology is deployed locally at scale). Thus, if current power sector trends continue, this may necessitate economically costly options—e.g. stranding fossil electrical assets, retrofitting existing plants with CCS, or offsetting increased emissions through mass deployment of carbon dioxide removal technologies [5, 37], which ultimately may come at a higher expense than early retirement. While the value of such generating capital and the total cost to society are represented and depreciated within these scenarios, the distribution of these costs is not. Therefore, lost revenues and profitability for plant owners and local governments, or job losses for workers might prove prohibitively high.

It should be noted that some of our projections of future emissions reported here do not allow lifetimes and capacity factors to vary over time, across regions, or between different generating assets which is in contrast to the flexibility allowed in power plant operational conditions both in the integrated assessment models and the real world. Thus, insofar as capacity factors and lifetimes may in reality decrease over the lifetime, operation, and retirements may be strategically scheduled, and plants might be mothballed and re-operated. Thus, the overshoot we project should be interpreted to reflect the capacity-weighted average lifetime and may be overestimated. However, we find it crucial to demonstrate the incapability of continued investments in fossil fuel power infrastructure with more ambitious climate mitigation scenarios rather than focus on any one single lifetime trajectory. That is, because it is newly commissioned power plants

that create the greatest inertia and scenario overshoot. While in some cases inertia and emissions could be avoided by extending the life of existing and due-to-retire plants, such that new plants will not have to be built (and the older plants can be more readily retired to rapidly decrease emissions), achieving such flexibility in reality would depend upon clear foresight of both regional electricity demand and global climate-energy policies, as well as rational economic behavior on the part of utilities and power plant owners whom historically have not been transparent in their decisions [38, 39]. Nonetheless, decarbonizing the global power sector is currently technically and economically feasible given proven technology but is contingent on the increased investment and construction of low-carbon technology and infrastructure as well as passing legislation regulating carbon emitting technologies [40]. While costly, the co-benefits to society often outweigh the overall financial burdens that result from a swift retirement of polluting plants [41]. Thus, policy makers should immediately begin to phase out fossil-fired power plants by supporting low-carbon energy infrastructure while simultaneously implementing legislation that's unfavorable for continued fossil fuel use. However, in reality, governments have been observed taking the opposite approach, choosing instead to prop up economically unstable power plants through subsidies and/or by passing industry favorable regulations in order to minimize the socioeconomic consequences of plant closures and ultimately prolonging the infrastructural inertia of these plants [39].

Thus, in conclusion, power sector capital that is amassed over decades will also take decades to retire unless its value is sacrificed, and lower-warming scenarios often demand such sacrifice. Which policy mechanisms force early retirements may ultimately determine who will bear the economic losses. In jurisdictions with strict climate policies, proactively limiting the time period that new coal- and gas-fired plants will be allowed to operate might forestall investments that would otherwise either contribute to emissions overshoot or else be forced to retire early at great expense. In the future, operating lifetimes and economic implications of CO₂ emitting-infrastructure should be considered when formulating future energy investments that are consistent with existing climate policies so that investors may determine the compatibility of their planned energy infrastructure investments with different scenarios of climate change and fully understand the risks of their monetary investments [18, 38].

2. Methods

2.1. Existing and historical infrastructure

We use the Global Power Plant Emissions Database (GPED) to analyze historical coal and gas power plants that are currently operating. We quantify

the annual electrical generation, installed nameplate capacity, yearly averaged emission intensities, and annual mean capacity factor of all existing and past power plants. For currently operating generators, we identify current installed capacity in each region and the year each was commissioned, and project the expected year of retirement based on an assumed lifetime.

2.2. Power infrastructure commissioned in future

Regional scenarios of future electricity projections were produced for each of the Shared Socioeconomic Pathways (SSPs) by the Asia-Pacific Integrated Model/Computable General Equilibrium (AIM/CGE), Global Change Assessment Model (GCAM), Integrated Model to Assess the Global Environment (IMAGE), the Model of Energy Supply Strategy Alternatives and their General Environmental Impacts—Global Biosphere Management (MESSAGE-GLOBIOM), Regional Model of Investments and Development—Model of Agricultural Production and its Impact on the Environment (REMIND-MAGPIE), and World Induced Technical Change Hybrid—Global Biosphere Management (WITCH-GLOBIOM) integrated assessment models (IAMs). Each IAM uses different number of regions to represent global society and classifies these regions based on their socioeconomics, geopolitics, and stage in economic development of the nations represented. A full list of IAM regions and associated historical mean capacity factors and carbon intensities is provided within the *supplementary information, tables 2–7*. We quantify existing power generating infrastructure, electricity demand, and generator operating conditions using the same regional classifications as represented in each IAM. We then project the need for new electricity generating capacity by estimating the difference between IAM projections and existing electrical capacity in each world region and SSP-model-radiative forcing trajectories.

Repeated analyses vary the assumed lifetimes of coal- and gas-fired power plants 10–60 years and capacity factors from 35%–75%, applicable to both existing generators and any infrastructure commissioned in the future. In our standardized approach, power generators are phased out once their expected operational lifetime has elapsed. New power generators are only built if the annual power supply dips below annual power demand, which can occur when existing power infrastructure is retired or if there is a sustained increase in power demand projected by the IAMs. Newly constructed generators are assumed to have the same operating conditions as the corresponding model run. Nonetheless, we calculate the 1.9 and 2.6 W m^{-2} radiative forcing scenarios required very little deployment of new coal-fired power plants, instead most of the overshoot observed in our results come from existing power infrastructure with the exemptions of a few regions globally.

2.3. Emissions

We convert our estimates of electricity generation to carbon dioxide emissions using IAM electricity projections, our energy calculations under different lifetime assumptions, and IAM regional mean historical carbon intensities ranging from 387–1381.4 $\text{gCO}_2 \text{ kWh}^{-1}$. Here we analyze 18 810 of individual IAM regional coal and gas electricity scenarios and categorically applied the corresponding carbon intensity. A detailed list of IAM regional mean carbon intensities can be found in the *supplementary information, tables 2–7*. Additionally, we use a linear regression approach and looked at the annual emission reductions 2017 to 2050, to determine the annual emission mitigation rates of each IAM-SSP included in this study. For each radiative forcing pathway, cumulative emissions overshoot was determined by taking the difference between the cumulative emission projection and the cumulative emissions trajectories under the various power plant lifetime assumptions used for this study. In each RF, cumulative emissions are calculated by model, SSP, and lifetime assumption individually then separated by their statistical distribution thus identifying the probability of the emissions trajectory.

2.4. Regional analysis

We analyze regional emissions under each of the IAMs included in this study using the mean IAM regional capacity factors and carbon emissions intensities. In each case, we calculate the cumulative emission overshoot for both coal-fired and natural gas electricity generation individually by RF, IAM, and SSP. We separate the cumulative emission overshoot by their statistical distribution to quantify the likelihood of this emission projection and plot the median cumulative carbon dioxide emissions in each case. Additionally, we identify the magnitude of CO_2 emission overshoot for each region based on historical median power plant lifetimes of 37 years. Regional calculations are based on IAM regional classifications and are aggregated to quantify global energy and emissions. In each case, we analyze global emissions overshoot for each of the radiative forcing trajectories included in this study. Here we calculated the overshoot and again vary the historical capacity factors by 35%–75% and vary the power plant lifetimes from 10–60 years. Using the GPED database, we estimate the historical capacity factors to be $\sim 65\%$ and $\sim 55\%$ for coal and gas power plants, respectively.

Acknowledgments

R.F. and S.J.D. were supported by the U.S. National Science Foundation (INFEWS grant EAR 1639318). D.T. was supported by NASA's IDS program (80NSSC17K0416).

Contributions

RF and SJD designed the study; RF led the analysis with additional input and data support from SJD, DT, KC, HSB, JE, OF, SE, GL, and JR; RF led the writing with input and revisions from all coauthors.

Data availability

The data that support the findings of this study are available from the corresponding author upon reasonable request

Conflict of interest

The authors declare no competing interests.

ORCID iDs

Robert Fofrich  <https://orcid.org/0000-0001-6418-3692>

Katherine Calvin  <https://orcid.org/0000-0003-2191-4189>

Johannes Emmerling  <https://orcid.org/0000-0003-0916-9913>

Shinichiro Fujimori  <https://orcid.org/0000-0001-7897-1796>

Gunnar Luderer  <https://orcid.org/0000-0002-9057-6155>

Joeri Rogelj  <https://orcid.org/0000-0003-2056-9061>

Steven J Davis  <https://orcid.org/0000-0002-9338-0844>

References

- [1] Davis S J *et al* 2018 Net-zero emissions energy systems *Science* **360** 1419
- [2] Rogelj J, Schaeffer M, Meinshausen M, Knutti R, Alcamo J, Riahi K and Hare W 2015 Zero emission targets as long-term global goals for climate protection *Environ. Res. Lett.* **10** 105007
- [3] Williams J H, DeBenedictis A, Ghanadan R, Mahone A, Moore J, Morrow W R, Price S and Torn M S 2012 The technology path to deep greenhouse gas emissions cuts by 2050: the pivotal role of electricity *Science* **335** 53–59
- [4] Audoly R, Vogt-Schillb A, Guivarch C and Pfeiffer A 2018 Pathways toward zero-carbon electricity required for climate stabilization *Appl. Energy* **225** 884–901
- [5] Luderer G *et al* 2018 Residual fossil CO₂ emissions in 1.5–2 °C pathways *Nat. Clim. Change* **8** 626–33
- [6] Davis S J, Caldeira K and Matthews H D 2010 Future CO₂ emissions and climate change from existing energy infrastructure *Science* **329** 1330–3
- [7] Taylor M J and Fuller L C 1986 *Coal-fired Electric Power Plant Life Extension: An Overview* (Oak Ridge, TN: Oak Ridge National Laboratory)
- [8] Davis S J and Soclow R H 2014 Commitment accounting of CO₂ emissions *Environ. Res. Lett.* **9** 084018
- [9] Seto K C, Davis S J, Mitchell R B, Stokes E C, Unruh G and Ürge-Vorsatz D 2016 Carbon lock-in: types, causes, and policy implications *Annu. Rev. Environ. Resour.* **41** 425–52
- [10] Rogelj J, Luderer G, Pietzcker R C, Kriegler E, Schaeffer M, Krey V and Riahi K 2015 Energy system transformations for limiting end-of-century warming to below 1.5 °C *Nat. Clim. Change* **5** 519–27
- [11] Rogelj J *et al* 2018 Scenarios towards limiting global mean temperature increase below 1.5 °C *Nat. Clim. Change* **8** 325–32
- [12] Wamsted D, Seth F and Schlissel D Coal Outlook 2019 - Domestic Market Decline Continues, The Institute for Energy Economics and Financial Analysis (IEEFA)
- [13] Gray M, Sebastian L, Watson L and Kok I 2018 Powering down coal - Navigating the economic and financial risks in the last years of coal power, Carbon Tracker Initiative
- [14] Gimon Eric O B M, Christopher C and Sarah M 2019 The Coal Cost Crossover: Economic Viability of Existing Coal Compared to New and Local Wind and Solar Resources, Energy Innovation
- [15] Baron R and Fischer D 2015 Divestment and stranded assets in the low-carbon transition, OECD
- [16] Tong D, Zhang Q, Zheng Y, Caldeira K, Shearer C, Hong C, Qin Y and Davis S J 2019 Committed emissions from existing energy infrastructure jeopardize 1.5 °C climate target *Nature* **572** 373–7
- [17] Battiston S, Mandel A, Monasterolo I, Schütze F and Visentin G 2017 A climate stress-test of the financial system *Nat. Clim. Change* **7** 283–8
- [18] Sen S and von Schickfus M-T 2020 Climate policy, stranded assets, and investors' expectations *J. Environ. Econ. Manage.* **100** 102277
- [19] Binsted M *et al* 2020 Stranded asset implications of the Paris Agreement in Latin America and the Caribbean *Environ. Res. Lett.* **15** 044026
- [20] Iyer G C *et al* 2015 The contribution of Paris to limit global warming to 2 °C *Environ. Res. Lett.* **10** 125002
- [21] Pfeiffer A, Millar R, Hepburn C and Beinhocker E 2016 The '2 °C capital stock' for electricity generation: committed cumulative carbon emissions from the electricity generation sector and the transition to a green economy *Appl. Energy* **179** 1395–408
- [22] Cui R Y *et al* 2019 Quantifying operational lifetimes for coal power plants under the Paris goals *Nat. Commun.* **10** 4759
- [23] Bertram C, Luderer G, Pietzcker R C, Schmid E, Kriegler E and Edenhofer O 2015 Complementing carbon prices with technology policies to keep climate targets within reach *Nat. Clim. Change* **5** 235–9
- [24] Platts 2018 World Electric Power Plant Database, Platts
- [25] Bauer N *et al* 2017 Shared socio-economic pathways of the energy sector-quantifying the narratives *Glob. Environ. Change* **42** 316–30
- [26] I. E. Agency 2019 Electricity Information 2019, IEA
- [27] Riahi K *et al* 2017 The shared socioeconomic pathways and their energy, land use, and greenhouse gas emissions implications: an overview *Glob. Environ. Change* **42** 153–68
- [28] Tong D *et al* 2018 Targeted emission reductions from global super-polluting power plant units *Nat. Sustain.* **1** 59–68
- [29] 2015 IAM helpful or not? *Nat. Clim. Change* **5** 81–81
- [30] Shearer C, Fofrich R and Davis S J 2017 Future CO₂ emissions and electricity generation from proposed coal-fired power plants in India *Earth's Future* **5** 408–16
- [31] Smith P *et al* 2016 Biophysical and economic limits to negative CO₂ emissions *Nat. Clim. Change* **6** 42–50
- [32] Matthews H D, Gillett N P, Stott P A and Zickfeld K 2009 The proportionality of global warming to cumulative carbon emissions *Nature* **459** 829–33
- [33] Allen M R, Frame D J, Huntingford C, Jones C D, Lowe J A, Meinshausen M and Meinshausen N 2009 Warming caused by cumulative carbon emissions towards the trillionth tonne *Nature* **458** 1163–6

- [34] Rogelj J, Forster P M, Kriegler E, Smith C J and Séférian R 2019 Estimating and tracking the remaining carbon budget for stringent climate targets *Nature* **571** 335–42
- [35] Meinshausen M, Meinshausen N, Hare W, Raper S C B, Frieler K, Knutti R, Frame D J and Allen M R 2009 Greenhouse-gas emission targets for limiting global warming to 2 °C *Nature* **458** 1158–62
- [36] Raupach M R, Davis S J, Peters G P, Andrew R M, Canadell J G, Ciais P, Friedlingstein P, Jotzo F, van Vuuren D P and Le Quéré C 2014 Sharing a quota on cumulative carbon emissions *Nat. Clim. Change* **4** 873–9
- [37] Kriegler E, Luderer G, Bauer N, Baumstark L, Fujimori S, Popp A, Rogelj J, Strefler J and van Vuuren D P 2018 Pathways limiting warming to 1.5 °C: a tale of turning around in no time? *Phil. Trans. R. Soc. A* **376** 20160457
- [38] Gerrard M B D and John C 2018 *Legal Pathways to Deep Decarbonization in the United States* (Washington, DC: Environmental Law Institute)
- [39] Jewell J, Vinichenko V, Nacke L and Cherp A 2019 Prospects for powering past coal *Nat. Clim. Change* **9** 592–7
- [40] Haley B, Ryan J, Kwok G, Hargreaves J and Farbes J 2019 350 PPM Pathways for the United States *Deep Decarbonization Pathways Project (DDPP)*, (San Francisco, CA: Evolved Energy Research)
- [41] Rauner S, Bauer N, Dirnacher A, Dingemans R V, Mutel C and Luderer G 2020 Coal-exit health and environmental damage reductions outweigh economic impacts *Nat. Clim. Change* **10** 308–12